Alpha Recessed

01

- Luminaire for fluorescent T16 G5 lamps.
- Recessed mounting for mineral fiber false ceiling.
- Body made of steel sheet powder coated.
- Double parabolic louver.
- Integrated electronic control gear.

CODE FOR MINERAL FIBER	8600	8600 DIM	8602	8604	8605
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Lamp Power (W)	4 x 14	4 x 14	4 x 24	3 x 14	3 x 24
Length (mm)	595	595	595	595	595
Width (mm)	595	595	595	595	595
CODE FOR PLASTERBOARD	**8601**	**8601 DIM**	**8603**	**8606**	**8607**
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Lamp Power (W)	4 x 14	4 x 14	4 x 24	3 x 14	3 x 24
Dimensions (mm)	595 x 595	595 x 595	595 x 595	595 x 595	595 x 595
Cut Out Ø (mm)	580 x 580	580 x 580	580 x 580	580 x 580	580 x 580

CODE FOR RECTANGULAR ALL TYPE CEILING	8630	8630 DIM	8631	8635	8636	8637	8637 DIM
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Lamp Power (W)	2 x 28	2 x 28	2 x 54	2 x 35	2 x 49	2 x 80	2 x 80
Length (mm)	1180	1180	1180	1480	1480	1480	1480
Width (mm)	205	205	205	205	205	205	205