

# Hermes Slim



- Hermes slim linear lighting system for single fluorescent T16 G5 lamp.
- Surface mounted or suspended.
- Body of extruded aluminium powder coated.
- Transparent acrylic diffuser.
- Integrated electronic HF control gear.
- Add Dim suffix for DSI dimmable control gear (other dimming options available upon request).
- For continuous light applications, luminaire housing and acrylic covers can be supplied up to 3.6 meters.
- Provided with direct ceiling installation elements.
- Different types of connectors for linear or corner configuration.

| CODE             | 4020    | 4024    | 4021    | 4025    | 4022    | 4027    | 4023    | 4029    |
|------------------|---------|---------|---------|---------|---------|---------|---------|---------|
| Frequency (Hz)   | 50/60   | 50/60   | 50/60   | 50/60   | 50/60   | 50/60   | 50/60   | 50/60   |
| Main Voltage (V) | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 |
| Lamp Power (W)   | 14      | 24      | 21      | 39      | 28      | 54      | 35      | 49      |
| Length (mm)      | 580     | 580     | 880     | 880     | 1180    | 1180    | 1480    | 1480    |
| Width (mm)       | 52      | 52      | 52      | 52      | 52      | 52      | 52      | 52      |

## CODE ACCESSORIES

|      |                                      |  |
|------|--------------------------------------|--|
| 4047 | Suspension with power supply cord    |  |
| 4048 | Suspension without power supply cord | (1 suspension required every 1,5 meters) |

FOR ACCESSORIES DETAILS SEE PAGE 155