



Hermes Twin



- Linear luminaire for two parallel single fluorescent T16 G5 lamp.
- Surface mounted or suspended.
- Body made of extruded aluminium powder coated.
- Parabolic louver, opal or transparent acrylic diffuser options.
- Integrated electronic HF ballast.
- Add Dim suffix for DSI dimmable ballast (other dimming options available upon request).
- Suspension cable to be ordered separately.
- Provided with direct ceiling installation elements.

CODE	4091	4092	4094	4096	4095
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (v)	220-240	220-240	220-240	220-240	220-240
Lamp Power (w)	2 x 28	2 x 54	2 x 35	2 x 80	2 x 49
Length (mm)	1180	1180	1480	1480	1480
Width (mm)	185	185	185	185	185

CODE SCREENS

Aluminium parabolic louver	2 x 4068	2 x 4068	2 x 4069	2 x 4069	2 x 4069
Acrylic transparent diffuser	2 x 4061	2 x 4061	2 x 4062	2 x 4062	2 x 4062
Acrylic opal diffuser	2 x 6155	2 x 6155	2 x 6156	2 x 6156	2 x 6156

CODE ACCESSORIES

4047	Suspension with power supply cord	
4048	Suspension without power supply cord	(1 suspension required every 1,5 meters)