


FLUORESCENT & METAL HALIDE



Ikarus



- Linear lighting system for fluorescent T16 G5 lamps.
- Surface mounted or suspended.
- Body made of extruded aluminium powder coated.
- Parabolic Louver, opal or transparent acrylic diffuser options.
- Integrated electronic HF ballast.
- Add Dim suffix for DSI dimmable ballast (other dimming options available upon request).
- For continuous light applications, luminaire housing and acrylic covers can be supplied up to 3.6 meters.
- Provided with direct ceiling installation elements.
- Different types of connectors for linear or corner configuration.

CODE	4306	4307	4308	4309	4310	4311	4312	4314
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Lamp Power (W)	2 x 14	2 x 24	2 x 21	2 x 39	2 x 28	2 x 54	2 x 35	2 x 49
Length (mm)	660	660	960	960	1260	1260	1560	1560
Width (mm)	88	88	88	88	88	88	88	88

CODE SCREENS

Aluminium parabolic louver	4341	4341	4342	4342	4343	4343	4344	4344
Acrylic transparent diffuser	4345	4345	4346	4346	4347	4347	4348	4348
Acrylic opal diffuser	4349	4349	4350	4350	4351	4351	4352	4352

CODE ACCESSORIES

4047	Suspension with power supply cord	
4048	Suspension without power supply cord	(1 suspension required every 1,5 meters)
4330	PC End cap	
4333	Metallic End cap	90 x 90mm
4331	Line connection cover	80mm
4055	Concealed Line Coupling Element	