



## Kanali 10



- Linear lighting system for dual fluorescent T16 G5 lamps.
- Recessed mounted.
- Body of extruded aluminium powder coated.
- Parabolic aluminium louver, opal or transparent acrylic diffuser options.
- Integrated electronic HF control gear.
- Add DIM suffix for DSI dimmable control gear (other dimming options available upon request).
- For continuous light applications, luminaire housing and acrylic covers can be supplied up to 3.6 meters.

CODE LIGHTING INSERT	4450	4451	4452	4453	4454	4455	4456	4457	4458
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Main Voltage (v)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Lamp Power (w)	14	24	21	39	28	54	35	80	49
CODE HOUSING MODULE	4445	4445	4446	4446	4447	4447	4448	4448	4448
Dimensions WxLxH (mm)	117x610x73	117x610x73	117x910x73	117x910x73	117x1210x73	117x1210x73	117x1510x73	117x1510x73	117x1510x73
Cut Out Ø (mm)	97 x 580	97 x 580	97 x 880	97 x 880	97 x 1180	97 x 1180	97 x 1480	97 x 1480	97 x 1480
CODE SCREENS									
Aluminium parabolic louver	4341	4341	4342	4342	4343	4343	4344	4344	4344
Acrylic transparent diffuser	4345	4345	4346	4346	4347	4347	4348	4348	4348
Acrylic opal diffuser	4349	4349	4350	4350	4351	4351	4352	4352	4352
CODE ACCESSORIES	<b>4465</b> End caps (pair)				<b>4503</b> Linear connectors (pair)				

FOR ACCESSORIES DETAILS SEE PAGE 155