



Kanali 19 Dark



- Linear lighting system for metal halide or halogen spots.
- Recessed mounted for plasterboard false ceiling.
- Body of extruded aluminium powder coated.
- The housing module has opening doors for easy control gear installation.
- Can be combined with KANALI 19 Fluorescent.



www.gallis.gr

CODE SPOT HOUSING	4510	4511	4512	4513			
Number of spots	1	2	2	3			
Dimensions WxLxH (mm)	198x2030x150	198x1030x150	198x630x150	198x430x150			
Cut Out Ø (mm)	171 x 2000	171 x 1000	171 x 600	171 x 400			
CODE FOR MID INSERT	4430	4431	4428	4432	4433	4429	4439
Lamp Power (w)	35/70 G12	35/70 G12	35/70 G12	35/70 G12	35/70 G12	35/70 G12	35/70 G12
Beams	10°	26°	26°	38°	58°	58°	98°
CODE FOR HQ INSERT	4434	4435	4436				
Lamp Power (w)	100	100	100				
Type	QPAR 30	QR-LP 111	ESD 111				
Lamp holder	E27	G53					
CODE FOR GEAR	0091L	0092L	0094L	0096L	0097L	Electronic transformer	
Power (w)	35	70	35/70	2 x 35	2 x 70	12V/60V 60W	
CODE ACCESSORIES					Dimensions (mm)	Weight (kg)	
4500	Spot Housing Plate (MORFEAS SPOTS)				220	0,1	
4504	Blind Module				220	0,28	
4501	End caps (pair)					0,3	
4502	L-Shape Housing Module				400	2,1	
4503	Linear connectors (pair)						

FOR ACCESSORIES DETAILS SEE PAGE 155