



Kanali 19



- Linear lighting system for dual fluorescent T16 G5 lamps and MORFEAS spots or combination of both.
- Recessed mounted.
- Body made of extruded aluminium powder coated.
- Parabolic aluminium louver for the fluorescent option.
- Various spot configuration (one to six spots mounting plate).
- Integrated electronic HF control gear.
- Add DIM suffix for DSI dimmable control gear (other dimming options available upon request).

| CODE | 4410 | 4411 | 4412 | 4413 | 4414 | 4415 | 4416 | 4417 |
|-------------------------|-----------------------------|------------|------------|--------------------------------------|-------------|-------------|-------------|-------------|
| Frequency (Hz) | 50/60 | 50/60 | 50/60 | 50/60 | 50/60 | 50/60 | 50/60 | 50/60 |
| Main Voltage (v) | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 |
| Lamp Power (w) | 2 x 14 | 2 x 24 | 2 x 21 | 2 x 39 | 2 x 28 | 2 x 54 | 2 x 35 | 2 x 80 |
| Dimensions WxLxH (mm) | 198x610x73 | 198x610x73 | 198x910x73 | 198x910x73 | 198x1210x73 | 198x1210x73 | 198x1510x73 | 198x1510x73 |
| Cut Out Ø (mm) | 180 x 580 | 180 x 580 | 180 x 880 | 180 x 880 | 180 x 1180 | 180 x 1180 | 180 x 1480 | 180 x 1480 |
| CODE ACCESSORIES | 4440 End caps (pair) | | | 4503 Linear connectors (pair) | | | | |

FOR ACCESSORIES DETAILS SEE PAGE 155