



Kanali Flameless

01



- Linear lighting system for single or dual fluorescent T16 G5 lamps.
- Recessed flameless mounted for plasterboard false ceiling.
- Body made of extruded aluminium powder coated.
- Opal or transparent acrylic diffuser options.
- Integrated electronic HF control gear.
- Add DIM suffix for DSI dimmable control gear (other dimming options available upon request).
- For continuous light applications, luminaire housing and acrylic covers can be supplied up to 3.6 meters.

CODE	4528	4529	4530	4531	4532	4533	4534	4535	4536
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Lamp Power (W)	14	24	21	39	28	54	35	49	80
Length (mm)	580	580	880	880	1180	1180	1480	1480	1480
Width (mm)	90	90	90	90	90	90	90	90	90
CODE	4520	4521	4522	4523	4524	4525	4526	4537	
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	
Lamp Power (W)	2 x 14	2 x 24	2 x 21	2 x 39	2 x 28	2 x 54	2 x 35	2 x 49	
Length (mm)	580	580	880	880	1180	1180	1480	1480	
Width (mm)	90	90	90	90	90	90	90	90	
CODE ACCESSORIES	4537 End caps (pair)			4540 Linear connectors (pair)					

FOR ACCESSORIES DETAILS SEE PAGE 155