



## Morfeas



- Recessed directional downlight for metal halide HIT-T G12 lamp.
- Recessed mounting for false ceiling.
- Tilttable 0-45°.
- Mounting plate made of steel sheet powder coated and polycarbonate ring.
- 5 beam spread aluminium reflector (10°, 26°, 38°, 58°, 98°).
- Mounting plates to be ordered separately.
- Electronic control gear to be ordered separately.
- Required spot housing plate.

CODE	4430	4431	4432	4433	4439
Lamp Power (W)	35/70	35/70	35/70	35/70	35/70
Beam	10°	26°	38°	58°	98°
Diameter (mm)	145	145	145	145	145
Height (mm)	118	118	118	118	118

CODE ACCESSORIES		Dimensions (mm)	Cut Out Ø (mm)
2580	Ceramix - Gypsum Plate	220 x 220	220 x 220
2570	Plato Dual - Metal Plate	170 x 522	170 x 522
2571	Plato Single - Metal Plate	170 x 170	170 x 170
2563	Spot Housing Plate Square - Metal Plate	250 x 250	220
2564	Spot Housing Plate Square - Metal Plate	165 x 165	145 x 145
2565	Spot Housing Plate Square - Metal Plate	200 x 200	185
0030	Red Chromatic Filter Optimum Performance for HIT lamp in 3000K		
0031	Green Chromatic Filter Optimum Performance for HIT lamp in 3200K		
0032	Blue Chromatic Filter Optimum Performance for HIT lamp in 4000K		
0033	Yellow Chromatic Filter Optimum Performance for HIT lamp in 3200K		

CODE GEAR	
0091L	Electronic Gear 35W
0092L	Electronic Gear 70W
0094L	Electronic Gear 35/70W