



## Synergy Asymmetric

01 26

- Linear lighting system for fluorescent T16 G5 lamps.
- Surface mounted or suspended.
- Body of extruded aluminium powder coated.
- Superpure aluminium asymmetric reflector for high efficiency and smooth light distribution.
- Integrated electronic control gear.
- Suspension cables to be ordered separately.
- Add Dim suffix for DSI dimmable control gear (other dimming options available upon request).

CODE	8871	8872	8873	8874	8875	8876	8877	8878	8879
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240	220-240
Lamp Power (W)	1 x 14	1 x 24	1 x 21	1 x 39	1 x 28	1 x 54	1 x 35	1 x 49	1 x 80
Length (mm)	640	640	940	940	1240	1240	1540	1540	1540
Width (mm)	227	227	227	227	227	227	227	227	227

CODE	8881	8882	8883	8884	8885
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Lamp Power (W)	2 x 28	2 x 54	2 x 35	2 x 49	2 x 80
Length (mm)	2430	2430	3030	3030	3030
Width (mm)	227	227	227	227	227

### CODE ACCESSORIES

4047	Suspension with power supply cord	
4048	Suspension without power supply cord	(1 suspension required every 1,5 meters)