



**CUSTOMIZED  
LENGTH  
UPON  
REQUEST**

# E-Free LED

01 03 26

- Linear Lighting LED fitting.
- Surface mounted or suspended.
- Body made of extruded aluminium polyester powder coating white black or grey.
- Based on LED Tridonic modules 350 mA, 3000K ,4000K.
- Opal polycarbonate diffuser.
- ALANOD reflector.
- Provided with direct ceiling installation equipment.
- Different types of connectors for linear.
- Dimming option DSI or Dali available.
- Emergency version for Codes 4702 & 4703.
- Luminaire life time > 50,000 hours at 80% of luminous flux.

CODE	4700	4701	4702	4703	4706 corner 90°
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Source Power (W)	12,7	19	25,4	31,7	12,7
System Power (W)	13,3	20	26,7	33,3	13,3
Lumen Source (lm)	1830/1960	2750/2940	3660/3920	4580/4900	1830/1960
Lumen Luminaire (lm)	1470/1570	2200/2360	2930/3140	3670/3930	1470/1570
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	565	845	1125	1405	315 x 315
Weight (Kg)	1	1,2	1,75	1,98	1,1

CODE	4700 M	4701 M	4702 M	4703 M	4706 M corner 90°
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Source Power (W)	16	24	32	40	16
System Power (W)	21	25,2	33,6	42	21
Lumen Source (lm)	2690/2810	4030/4220	5380/5620	6720/7030	2690/2810
Lumen Luminaire (lm)	2150/2250	3225/3380	4310/4500	5380/5630	2150/2250
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	565	845	1125	1405	315 x 315
Weight (Kg)	1	1,2	1,75	1,98	1,1

ACCESSORIES CODE	
4047	Suspension cable with power supply
4048	Suspension cable without power supply
4707	End Caps (pair)
4055	Linear connectors (pair)

FOR ACCESSORIES DETAILS SEE PAGE 155