



Can be combined with Starlight Linear

CUSTOMIZED LENGTH UPON REQUEST

Kanali 40 Deep Starlight

01 03 26

- Indoor recessed linear LED lighting system for continuous light lines installation.
- Recessed for plasterboard false ceiling.
- Body made of extruded aluminium powder coated white, black or metallic-grey.
- Polycarbonate diffuser.
- Correlated Color Temperature (CCT) 3000K, 4000K, (single 3-step MacAdam ellipse), CRI >80.
- Based on LED modules of length 280mm.
- No shadows between modules. Homogeneous light distribution.
- Highly efficient passive cooling system with large surface on top of luminaire for heat management.
- End-caps to be ordered separately.
- LED driver integrated.
- Luminaire life time > 50,000 hours at 70% luminous flux.
- Can be combined with Starlight Linear spot. (see page 065)

CODE	1020 L	1021 L	1022 L	1023 L	1024 L
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Source Power (W)	12,7	19	25,4	31,7	38,1
System Power (W)	13,3	20	26,7	33,3	40
Lumen Source (lm)	1830/1960	2750/2940	3660/3920	4580/4900	5490/5880
Lumen Luminaire (lm)	1470/1570	2200/2360	2930/3140	3670/3930	4400/4705
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	600	875	1151	1440	1720
Cut out (mm)	591 X 40	870 x 40	1145 x 40	1429 x 40	1709 x 40
Weight (Kg)	1,3	1,5	1,9	2,2	2,5

CODE	1020 M	1021 M	1022 M	1023 M	1024 M
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Source Power (W)	16	24	32	40	48
System Power (W)	21	25,2	33,6	42	50,4
Lumen Source (lm)	2690/2810	4030/4220	5380/5620	6720/7030	8070/8430
Lumen Luminaire (lm)	2150/2250	3225/3380	4310/4500	5380/5630	6460/6750
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	600	875	1151	1440	1720
Cut out (mm)	591 x 40	870 x 40	1145 x 40	1429 x 40	1709 x 40
Weight (Kg)	1,3	1,5	1,9	2,2	2,5

ACCESSORIES CODE	
1029	End Caps (pair)
1028	Linear connectors (pair)