



Trigono

01 03 26

- Triangular linear lighting fitting equipped with TRIDONIC LED modules.
- Surface mounted or for corner installation.
- Body made of extruded aluminium powder coated with opal PC diffuser.
- Rotating arm options for up to 360° rotation. (To be ordered separately). Arm size 30mm
- Integrated LED Driver.
- Dimming options available upon request.

CODE	L-3010-M	L-3011-M	L-3012-M	L-3013-M
Frequency (Hz)	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240
Source Power (W)	16	24	32	40
System Power (W)	21	25,2	33,6	42
Lumen Source (lm)	2690/2810	4030/4220	5380/5620	6720/7030
Lumen Luminaire (lm)	2150/2250	3225/3380	4310/4500	5380/5630
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	580	900	1180	1480
Weight (kg)	1,5	2,1	2,6	3,2

CODE	L-3010-L	L-3011-L	L-3012-L	L-3013-L
Frequency (Hz)	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240
Source Power (W)	12,7	19	25,4	31,7
System Power (W)	13,3	20	26,7	33,3
Lumen Source (lm)	1830/1960	2750/2940	3660/3920	4580/4900
Lumen Luminaire (lm)	1470/1570	2200/2360	2930/3140	3670/3930
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	580	900	1180	1480
Weight (kg)	1,5	2,1	2,6	3,2

ACCESSORIES CODE	
3050	Fixed End cap (pair)
3051	Rotating End cap (pair)
3052	Rotating Arm (pair) H70mm Rotation 45°/270°
3053	Rotating Arm (pair) H100mm Rotation 360°
3054	Rotating Arm (pair) H250mm Rotation 360°
3055	Suspension cable without power supply cord (pair)
3056	Ceiling Attachment Elements (pair)
3057	Line connection Cover (External)
4055	Concealed Line coupling element