



Forever Downlight

22

- Indoor and outdoor waterproof ceiling recessed LED downlight.
- Full luminaire made of machined aluminium to optimize heat dissipation.
- Clear protection plastic glass 6 mm, silicon rings.
- Nichia LED mounted on metal core PCB (MCPCB) 2700K, 3000K and 4000K.
- European beam shaping lens.
- Anticorrosion capabilities through the anodization process implemented on the aluminium parts.
- Minimum thickness of the anodized layer is 20µm.
- For outdoor or corrosive environments (i.e. seaside or industrial spaces).
- 10 years warranty of the body.
- Also available in electrostatic polyester powder coated version 10µm coating, for outdoor use, but not Seaside Class.
- Available filter colors: green, yellow, red.
- CRI 90 available upon request.
- Luminaire life time > 50,000 hours at 70% luminous flux.
- LED driver to be ordered separately.
- EMERGENCY VERSION UPON REQUEST.
- Multiple spots can be operated through one CC driver in serial connection.
- Dimmable.

CODE	1152	1152 SQ
Max Input (mA)	700 DC	700 DC
Source Power (W)	2,1	2,1
Lumen Source (lm)	280	280
Lumen Luminaire (lm)	224	224
CCT (K)	3000	3000
Beams	14°,28°,44° & 14° +48°	14°,28°,44° & 14° +48°
CRI	≥ 80	≥ 80
Cut Out Ø (mm)	50	50
Weight (Kg)	0,15	0,15

CODE ACCESSORIES

CO.016 Anti-glare Honey comb

FOR ACCESSORIES DETAILS SEE PAGE 156