



1145BR



1145AL



1144BR



1144AL



1143BR



1143AL

Forever LED



- Indoor and outdoor waterproof ground recessed LED series.
- Full luminaire made of machined aluminium 6262 or Brass MS 58 to optimize heat dissipation.
- Grey anodized aluminium.
- Clear protection PC 6mm, silicon rings.
- Nichia LED mounted on metal core PCB (MCPCB). 2700K-3000K-4000K.
- Anti-corrosion capabilities through the anodization process implemented on the aluminium parts.
- Included installation tube.
- Minimum thickness of the anodized layer is 20µm for outdoor or corrosive environments (i.w seaside or industrial spaces).
- The anodization process fulfills the criteria of Seaside Class.
- 10 years warranty on the body.
- Luminaire life time > 50,000 hours at 70% luminous flux.
- Available @700mA.
- Non dimmable.

CODE	1143AL	1143BR	1144AL	1144BR	1145AL	1145BR
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60
Main Voltage (v)	220-240	220-240	220-240	220-240	220-240	220-240
Source Power (w)	2,1	2,1	2,1	2,1	2,1	2,1
System Power (w)	2,2	2,2	2,2	2,2	2,2	2,2
Lumen Source (lm)	280	280	280	280	280	280
Lumen Luminaire (lm)	224	224	224	224	224	224
CCT (K)	3000	3000	3000	3000	3000	3000
Beams	1	1	2	2	4	4
CRI	≥ 80	≥ 80	≥ 80	≥ 80	≥ 80	≥ 80
Cut Out Ø (mm)	D50xH130	D50xH130	D50xH130	D50xH130	D50xH130	D50xH130
Weight (Kg)	0,32	0,32	0,32	0,32	0,32	0,32

CODE ACCESSORIES

Filter	Red	Yellow	Blue	Green
CO.002	IP68 Connection, 3 poles			
CO.004	Cable Ho5RN-F 3G0,75 per meter			

FOR ACCESSORIES DETAILS SEE PAGE 156