



Plastic recessed fixing kit Included

# Forever LED



- Indoor and outdoor waterproof ground recessed LED series.
- Full luminaire made of machined aluminium 6262 or Brass MS 58 to optimize heat dissipation.
- Grey anodized aluminium.
- Clear protection PC 6mm, silicon rings.
- Nichia LED mounted on metal core PCB (MCPCB). 2700K-3000K-4000K.
- Anti-corrosion capabilities through the anodization process implemented on the aluminium parts.
- Included installation tube.
- Minimum thickness of the anodized layer is 20µm for outdoor or corrosive environments (i.w seaside or industrial spaces).
- The anodization process fulfills the criteria of Seaside Class.
- 10 years warranty on the body.
- Luminaire life time > 50,000 hours at 70% luminous flux.
- Multiple spots can be operated through one CC driver in serial connection.
- MAX Input 700mA.
- Dimmable.

| CODE                 | 1153AL  | 1153BR  | 1154AL  | 1154BR  | 1155AL  | 1155BR  |
|----------------------|---------|---------|---------|---------|---------|---------|
| Max Input (mA)       | 700 DC  | 700 DC  | 700 DC  | 700 DC  | 700 DC  | 700 DC  |
| Source Power (W)     | 2,1     | 2,1     | 2,1     | 2,1     | 2,1     | 2,1     |
| Lumen Source (lm)    | 280     | 280     | 280     | 280     | 280     | 280     |
| Lumen Luminaire (lm) | 224     | 224     | 224     | 224     | 224     | 224     |
| CCT (K)              | 3000    | 3000    | 3000    | 3000    | 3000    | 3000    |
| Beams                | 1       | 1       | 2       | 2       | 4       | 4       |
| CRI                  | ≥ 80    | ≥ 80    | ≥ 80    | ≥ 80    | ≥ 80    | ≥ 80    |
| Cut Out Ø (mm)       | D50xH70 | D50xH70 | D50xH70 | D50xH70 | D50xH70 | D50xH70 |
| Weight (Kg)          | 0,32    | 0,32    | 0,32    | 0,32    | 0,32    | 0,32    |

## CODE ACCESSORIES

| Filter | Red                            | Yellow | Blue | Green |
|--------|--------------------------------|--------|------|-------|
| CO.001 | IP68 Connection, 2 poles       |        |      |       |
| CO.003 | Cable Ho5RN-F 2X0,75 per meter |        |      |       |

FOR ACCESSORIES DETAILS SEE PAGE 156