



Plastic recessed fixing kit Included



# Forever LED



- Indoor and Outdoor waterproof wall recessed mounted LED luminaire.
- Full luminaire made of machined aluminium 6262 or Brass MS 58 to optimize heat dissipation.
- Grey anodized aluminium or painted finish.
- Clear protection PC 6mm, silicon rings.
- Nichia LED mounted on metal core PCB (MCPCB). 2700K-3000K-4000K.
- CRI 90 available upon request.
- Anti-corrosion capabilities through the anodization process implemented on the aluminium parts.
- Included installation tube.
- Minimum thickness of the anodized layer is 20µm for outdoor or corrosive environments (i.w seaside or industrial spaces).
- The anodization process fulfills the criteria of Seaside Class.
- 10 years warranty on the body.
- Luminaire life time > 50,000 hours at 70% luminous flux.
- Available @700mA.
- Non dimmable.

CODE	1162	1162BR	1144/90°	1144BR/90°
Frequency (Hz)	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240
Source Power (W)	2,1	2,1	2,1	2,1
System Power (W)	2,2	2,2	2,2	2,2
Lumen Source (lm)	280	280	280	280
Lumen Luminaire (lm)	224	224	224	224
CCT (K)	3000	3000	3000	3000
Beams	1	1	2 @ 90°	2 @ 90°
CRI	≥ 80	≥ 80	≥ 80	≥ 80
Cut Out Ø (mm)	D50xH130	D50xH130	D50xH130	D50xH130
Weight (Kg)	0,32	0,32	0,32	0,32

CODE ACCESSORIES	
CO.002	IP68 Connection, 3 poles
CO.004	Cable Ho5RN-F 3G0,75 per meter

FOR ACCESSORIES DETAILS SEE PAGE 156