



Forever LED Ceiling

22 03

- Outdoor waterproof surface mounted LED series.
- Full luminaire made of machined aluminium 6262 to optimize heat dissipation.
- Grey anodized aluminium or painted finish. Clear protection PC 6mm, silicon rings.
- Nichia LED mounted on metal core PCB (MCPCB).
- Available 2700K, 3000K and 4000K.
- CRI 90 upon request.
- Luminaires with integrated LED driver.
- Anti-corrosion capabilities through the anodization process implemented on the aluminum parts.
- Minimum thickness of the anodized layer is 20µm for outdoor or corrosive environments (i.e. seaside or industrial spaces).
- The anodization process fulfils the criteria of Seaside Class.
- 10 years warranty on the body.
- Luminaire life time > 50,000 hours at 70% luminous flux.
- Available @350mA or 700mA.
- Non dimmable.

| CODE | 1163 | 1163 |
|----------------------|---------------------------|---------------------------|
| Frequency (Hz) | 50/60 | 50/60 |
| Main Voltage (v) | 220-240 | 220-240 |
| Source Power (w) | 2,1 | 1,05 |
| System Power (w) | 2,2 | 1,1 |
| Driven @ (mA) | 700 | 350 |
| Lumen Source (lm) | 280 | 140 |
| Lumen Luminaire (lm) | 224 | 112 |
| CCT (K) | 3000 | 3000 |
| Beams | 14°,28°,44° & 14° +48° | 14°,28°,44° & 14° +48° |
| CRI | ≥ 80 | ≥ 80 |
| Weight (Kg) | 0,36 | 0,36 |

| CODE ACCESSORIES | Red | Yellow | Blue | Green |
|------------------|-----|--------|------|-------|
| Filter | | | | |

FOR ACCESSORIES DETAILS SEE PAGE 156