



# Sirius LED Colors

01 03 26

- Exterior Color LED multipurpose adjustable projector made in diecast aluminum.
- Clear protection glass, silicon rubber gaskets and stainless steel screws.
- Wall/Ground fixation.
- Bracket with double pivot design for maximum adjustable flexibility (2 x 180°).
- Fixing base plate rotatable 170°.
- Electrostatic polyester powder coated black, white or alu-grey.
- Passive cooling (no moving parts).
- The luminaire is suitable for outdoor use, with ambient temperature (on the luminaire) from -40°C to +60°C.
- Uses 12 pcs of Nichia LED COLORS COB (RED or GREEN or BLUE)
- Luminaire life time > 50,000 hours at 70% luminous flux.
- Non Dimmable Driver Included. Dimming drivers available upon request.

CODE	4612R	4612G	4612B
Frequency (Hz)	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240
Source Power (W)	12	12	12
System Power (W)	13	13	13
Lumen luminaire (lm)	900	1668	480
Color	RED	GREEN	BLUE
Beams	14° 28° 44°	14° 28° 44°	14° 28° 44°
Weight (Kg)	2,59	2,59	2,59

CODE ACCESSORIES	
CO.019	Anti-glare snoot
CO.002	IP68 Connection, 3 poles
CO.004	Cable Ho5RN-F 3G 0,75 per meter
CO.022	Twin Spike plate for Sirius