



# Vivo Adjustable

01 03 26

- Indoor ceiling recessed fully adjustable LED downlight.
- All elements made of die cast aluminium, electrostatically polyester powder coated.
- Tilttable : 36° - Rotation 350°.
- Extruded aluminium passive cooling system black anodized for optimal heat dissipation.
- No moving parts.
- Equipped with TRIDONIC LED module.
- Polished anodized aluminium reflector, optimized for Zhaga book 3 LED modules.
- Clear protection glass. Stainless steel springs.
- CRI 90 available upon request.
- Luminaire life time > 50,000 hours at 70% luminous flux.
- LED driver to be ordered separately.
- EMERGENCY VERSION UPON REQUEST.

CODE	3450	3450	3450	3451
Max Input (mA)	500 DC	700 DC	1050 DC	1050 DC
Source Power (w)	17	25	33	38
Lumen Source (lm)	2730/2840	3630/3780	4530/4720	5620/5730
Lumen Luminaire (lm)	2185/2280	2910/3030	3630/3780	4500/4590
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000
Beams	24° ,55°	24° ,55°	24° ,55°	24° ,55°
CRI	≥ 80	≥ 80	≥ 80	≥ 80
Cut Out Ø (mm)	160	160	160	160
Weight (Kg)	0,96	0,96	0,96	0,96