

EN - Safety instructions - Installation instructions

Profi

- 1- Installation and commissioning may only be carried out by authorized specialists. Plaster housing should be installed by the false ceiling installer. Electrical components must be connected by qualified electrician.
- 2- BEWARE! Make sure the luminaires are always disconnected from the mains supply during wiring, installation and maintenance work. Before starting the installation, make sure the power is switched off.
- 3- This fixture is suitable for indoor use only (not suitable for wet area). The luminaire is exclusively used for lighting and is to be installed in accordance with the national regulations. Any other use or installation is regarded as "non according to instructions".
- 4- The luminaire with F mark are suitable for installation on normally flammable surfaces.
- 5- Always be sure to keep a minimum spacing of more than 0.5m (50cm) between the luminaire and the illuminated surface.
- 6- Do not cover the luminaire. Be really careful with insulating material. Avoid excess of dust deposition over the luminaire.
- 7- **Ceiling installation only:**

Make a **rectangular hole** in the plasterboard ceiling according to table below.

PROFI			
Code	Cut Out Dimension mm	Code	Cut Out Dimension mm
1043-118	$\phi = 210$	1043-132	$\phi = 210$
1043-218	$\phi = 210$	1043-232	$\phi = 210$
1043-126	$\phi = 210$	1043-142	$\phi = 210$
1043-226	$\phi = 210$		

Take the mains cable and pass it through the hole.

Connect the mains cable to the terminal block of the luminaire.

Pass the cable in the cable clamp and screw it tight.

8- Insert the luminaire in the hole in the ceiling

9- Place / replace the lamps.

Protection class I. The ground cable (green/yellow) must be connected. If there is not a mains supply with a protective ground wire available, the product must not be connected /used there.



IP 65



KEEP THESE INSTRUCTIONS FOR FURTHER REFERENCE.